

# LCD Customer Display



## WD-304U or WD-304R

Number of columns : 30 columns x 4 line

Interface : USB / Powered by USB or RS232 / Powered by COM



POS/ECR



Black

### No Power Supply Needed

#### Specification

Model	WD-304U or WD-304R	
Display method	LCD graphic display (blue purple)	
Number of columns	30 columns x 4 line	
Brightness	180 cd/m <sup>2</sup>	
Character type	8 x 16 dot matrix and graphic	
Character size	4.24 x 8.48 mm	
Fonts	96 alphanumeric, 11 international, 11 code page, Chinese, Japanese and Thai	
Command and driver	ESC/POS and OPOS	
MTBF (power on time)	20,000 hours	
Viewing angle	0 ~ 45 degree	
Rotating angle	270 degree (Max.)	
Power supply	Powered by USB / Powered by COM	
Power consumption	2.5W	
Interface	USB or RS232	
Gross weight	1.7 kg	
External dimension	Long	225 (W) x 100 (D) x 500 (H) mm
	Middle	225 (W) x 100 (D) x 281 (H) mm
	Short	225 (W) x 100 (D) x 193 (H) mm
Temperature	Operating	0 ~ 45°C
	Storage	-10 ~ 50°C
Humidity	Operating	10 ~ 90 %RH
	Storage	10 ~ 90 %RH