

QuantumT 3580

Omnidirectional Laser Scanner

Honeywell's QuantumT® 3580 provides retailers with industry-leading omnidirectional scan performance and optional single-line scanning in a convenient size. The small footprint and numerous stand options for QuantumT minimize required counter space, increasing available room for merchandise and advertisement displays.

Ideal for presentation scanning in moderate-volume retail environments such as convenience stores, liquor stores and pharmacies, end users can individually customize the scan pattern and operate the scanner in either a hand-held or hands-free fashion. In addition, its rugged, rubber housing provides the necessary protection against daily operational use.

QuantumT, with an industry-leading 1,650 scans/second, provides aggressive first-pass scanning, reducing the time it takes to scan products, increasing customer satisfaction and employee efficiency. The single-line scan feature, enabled by the push of a button, saves time and reduces unwanted scans on menu-style codes by providing targeted scanning through Honeywell's patented CodeGate® technology. Hand-held operation ensures easy scanning of larger, bulkier products that cannot be easily presented to stationary scanners.

QuantumT can be positioned at the user's convenience: mounted to a wall or countertop, atop one of four optional stands, or free standing for easy hand-held use. Other key features include Honeywell's patented IR activation mode, user-replaceable Powerlink cables and Flash memory.



Features

- **Omnidirectional/Single-Line Mode:** Alternate between 20 scan lines for omnidirectional scanning and a single scan line for menu scanning
- **Sleep Mode with IR Wake-Up:** Multiple sleep modes reduce power consumption, extending life and lowering cost of operation
- **Small Footprint:** Keeps valuable counter space clear
- **Optional Stands:** Customize the height of the scanner for unique applications
- **OPOS and JPOS System Compatible:** Easily adaptable to any end-user environment

QuantumT 3580 Technical Specifications

Mechanical

Dimensions (LxWxH) 66 mm x 67 mm x 108 mm (2.6" x 2.7" x 4.3")

Weight 170 g (6 oz)

Electrical

Input Voltage 5 VDC \pm 0.25 V

Operating Power 1.4 W (275 mA @ 5 V)

Standby Power 1.2 W (230 mA @ 5 V)

Host System Interfaces USB, RS232, Keyboard Wedge, IBM 46xx (RS485), OCIA, Laser Emulation, Light Pen Wand Emulation

Environmental

Operating Temperature -20°C to 40°C (-4°F to 104°F)

Storage Temperature -40°C to 60°C (-40°F to 140°F)

Humidity 5% to 95% relative humidity, non-condensing

Drop Designed to withstand 1.5 m (5') drops

Environmental Sealing Sealed to resist airborne particulate contaminants

Light Levels 4842 Lux

Scan Performance

Scan Pattern Omnidirectional: 5 fields of 4 parallel lines; Button activated single line

Scan Speed Omnidirectional: 1650 scan lines per second; Single line: 80 scan lines per second

Print Contrast 35% minimum reflectance difference

Pitch, Skew 60°, 60°

Decode Capability Reads standard 1D and GS1 DataBar symbologies

Warranty 3 year factory warranty

For a complete listing of all compliance approvals and certifications please visit www.honeywellaidc.com/compliance

For a complete listing of all supported bar code symbologies please visit www.honeywellaidc.com/symbologies



For more information:

www.honeywellaidc.com

Typical Performance*	
Narrow Width	Depth of Field
5.2 mil	38 mm - 101 mm (1.5" - 4.0")
7.5 mil	19 mm - 184 mm (0.8" - 7.3")
10.4 mil	19 mm - 235 mm (0.8" - 9.3")
13 mil	19 mm - 273 mm (0.8" - 10.8")
26 mil	19 mm - 298 mm (0.8" - 11.8")

*Resolution: 5 mil (0.125 mm)
*Performance may be impacted by bar code quality and environmental conditions

Honeywell