

VE-1519



Processor (CPU)	Intel Celeron J1900 Quad core 2.0GHz	Intel Celeron J3455 Quad core 2.3GHz
ChipSet	CPU Integrated	CPU Integrated
Memory (RAM)	DDR3 1.5V 1333MHz, 4GB	
HDD / SSD	SATA-III (6Gb/s) mSATA (64GB,128GB)	
Display (Front-LCD)	15", LVDS, 1024 X 768	
Display (Rear-LCD)	1 EA VGA (Intel® HD Graphics)	
Touch Panel	15", Capacitive P-CAP	
LAN	1 EA	
Serial (RS-232C)	2 EA (DSUB-9P X 2EA) Support Powered-COM2 (Select 0V/5V/12V by Jumper)	
VGA	1 EA	
USB	6 EA	
Audio	2 EA(1x Line out, 1x Mic-in)	
Speaker	0 EA	
Expansion Interface	mini-PCIe	
Cooler & FAN	Fanless	
Power Adaptor (External)	60[W] Adaptor Input AC 100~240V/50~60HZ, DC 12V/5.0A	
Tilt Adjustment	0° ~ 90°	
Dimension (W x H x D) (mm)	T.B.D 42*38.5*27.5CM(1pcs), 60*45*40CM(2pcs into 1caton)	
Weight (W/ STAND)	7.5KG(1pc) / 16KG(2pcs into 1 carton)	
OS	win 10, win7	

OPTION

MSR	MSR123
Dual Display	12.1", 15" dual monitor
CDP(VFD)	2X20 VFD
Wall Mount	75x75 CM



Vectronix System Inc. <http://www.vectronix.com.tw>

TEL:886-2-8227-3177 FAX:886-2-8227-3167

4F.-1, No.268, Liancheng Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)