

Barcode/MSR Slot Reader

MBR/BR

MBR1/2



Specification

- **Light Source** Visible Red light 632nm LED or Infrared ray 940nm
- **Operating Voltage** DC 5V \pm 5%
- **Power Consumption** 60mA
- **Sensor** Photo Diode
- **Scanning Speed** 100-1000mm/sec
- **Scanning Height** 10.5mm
- **Resolution** 0.15mm (6mil)
- **Interface** KBW,RS232,USB、TTL、ABA
- **Dimension** 100x27x26 mm / 90x27x26 mm

BR300



Specification

- **Light Source** Visible Red light 632nm LED or Infrared ray 940nm
- **Operating Voltage** DC 5V \pm 5%
- **Power Consumption** 80mA
- **Scanning Speed** 100-1000mm/sec
- **Scanning Height** 10.5mm
- **Print Contrast Ratio** PCS0.3 @0.15mm
- **Resolution** 0.15mm (6mil)
- **Interface** Combo(KBW,RS232,USB)、TTL
- **Dimension** 90 x 29 x38 mm

MMR/MR

MMR1/2



Specification

- **Operating Voltage** DC 5V \pm 5%
- **Power** 65mA
- **Scan Rate** 100~1000mm/sec
- **Track Information** Single Track(1st、2nd、3rd Track)
Dual Tracks(1&2、2&3 Tracks)
Tripe Tracks (1&2&3 Tracks), JIS II
- **Interface** Combo(KBW,RS232,USB)、TTL
- **Life Cycle** 300,000passes
(1,000,000 passes is optional)
- **Dimension (mm)** 100x27x26 mm / 90x22.5x14 mm

MR300



Specification

- **Operating Voltage** DC 5V \pm 5%
- **Power** 65mA
- **Scan Rate** 100~1000mm/sec
- **Interface** Combo(KBW,RS232,USB)、TTL
- **Life Cycle** 300,000passes
(1,000,000 passes is optional)
- **Dimension** 90x29x36 mm