

EP-382C

3" MICRO PANEL PRINTER WITH AUTO-CUTTER

- Easy-installing design
- Smart appearance
- Easy paper loading
- Low noise thermal printing
- Different interface optional
- Printer's cover lock



| | | |
|--------------------------|------------------------------|---|
| MODEL | | EP-382CL EP-382CH |
| Print | Thermal line printing | Thermal Line Printing |
| | Max Printing Speed | Max:150mm/s Max:180mm/s |
| | Resolution | 203dpi (8dots/mm) |
| Character | Effective printing width | 72mm |
| | Character Set | ASCII, GBK, BIG5 etc |
| | Print Font | ANK:9×17,12×24,GBK:24×24 |
| Character Flash | | 2M byte |
| MCU | | Flash:128KB SRAM:20KB |
| Paper spec | Paper Type | Thermal Paper |
| | Paper Width | 79.5±0.5mm |
| | Paper Roll Diameter | Max:80mm Min:13mm |
| | Paper Thickness | 55-90µm |
| Reliability | TPH | 100km or more (12.5% print ratio) |
| | Cutter | 1,000,000 cuts or more |
| Barcode | 1D | UPC-A,UPC-E,JAN/EAN-13,JAN/EAN-8,CODE39 |
| | 2D | ITF,CODABAR,CODE93,CODE128 |
| Cutting Method | | Full and Partial cut |
| Text and graphic support | | Figure,sample,graph,curve icon,multi-languages |
| Command | | Compatible with ESC/POS command set |
| Detctors | | paper end, paper near end, paper out, paper taken out, cover open |
| Interface | | Serial(RS232/TTL)+USB,Cash Drawer port (optional) |
| Power Supply(Adapter) | | DC12-24V/4A Peak current≥5A DC24V/2A Peak current≥3A |
| Driver | | Windows Driver;Linux Driver Windows/Android SDK |
| Physical | Outline Dimension | 118.7×136.1×87.5mm |
| | Installation Port Size (W×L) | 130.7×113.3mm |
| | Insert Depth | >85mm |
| | Color | Black/White |
| Environment | Operating temp | 0°C~50° |
| | Operating Humidity | 10%~80% |
| | Storage Temp | -20°C~60° |
| | Storage Humidity | 5%~90% |

